



TECHNICAL SPECIFICATIONS	Ténéré 700
ENGINE	
Engine type	2-Cylinder, 4-stroke, liquid-cooled, DOHC, 4-valves
Displacement	689 cm ³
Bore x stroke	80.0 mm x 68.6 mm
Compression ratio	11.5 : 1
Maximum power	54.0kW @ 9,000 rpm
Maximum torque	68.0Nm @ 6,500 rpm
Lubrication system	Wet sump
Clutch type	Wet, Multiple Disc
Carburettor	Fuel Injection
Ignition system	TCI
Starter system	Electric
Transmission system	Constant Mesh, 6-speed
Final transmission	Chain
Fuel consumption	N/A
CO ² emission	N/A
CHASSIS	
Frame	Double cradle steel tube chassis
Front suspension system	Upside down telescopic fork
Front travel	210mm
Caster Angle	N/A
Trail	N/A
Rear suspension system	Swingarm (link suspension)
Rear travel	200mm
Front brake	Hydraulic dual disc, Ø 282 mm
Rear brake	Hydraulic single disc, Ø 245 mm
Brake system	ABS
Front tyre	90/90 R21 M/C 54V M+S - Spoke wheels with Pirelli Scorpion Rally STR
Rear tyre	150/70 R18 M/C 70V M+S - Spoke wheels with Pirelli Scorpion Rally STR
DIMENSIONS	
Overall length	2,365 mm
Overall width	915 mm
Overall height	1,455 mm
Seat height	880 mm
Wheel base	1,590 mm
Minimum ground clearance	240 mm
Wet weight (including full oil and fuel tank)	N/A
Fuel tank capacity	16L
Oil tank capacity	N/A
ADDITIONAL FEATURE(S)	
Emission standard	EU4 compliant

Specification are subject to change without notice, in accordance with national regulation and legislations